

# CERTIFICATE OF CONSTANCY OF PERFORMANCE

0751-CPR.2-008.3-01

In compliance with Regulation (EU) 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

**Factory made mineral wool (MW) products for thermal insulation of building  
equipment and industrial installations**  
(details cf. annex)

Placed on the market under the name or trade mark of

**Rockwool Polska SP z o.o.**

Kwiatowa 14  
66-131 Cigacice  
Poland

and produced in the manufacturing plant

**Rockwool B.V.**

Industrieweg 15  
6040 KD Roermond  
Netherlands

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

**EN 14303:2009+A1:2013**

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the

**constancy of performance of the construction product.**

This certificate was first issued on 09.09.2016 and will remain valid (but no longer than 03.07.2023) as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

Gräfelfing, 03.07.2022



Certification Body

*Ralph Alberti*  
Ralph Alberti

A publication of extracts or a referring to the Certificate of Constancy of Performance and its annex requires the prior written approval of FIW München. Certification body accredited by DAkkS according to EN/ISO IEC 17065:2013 according to the certification annex D-ZE-14116-01-00.

Factory:

Rockwool B.V., Industrieweg 15, 6040 KD Roermond, Netherlands

Construction product(s):

Factory made mineral wool (MW) products for thermal insulation of building equipment and industrial installations according to EN 14303:2009+A1:2013

Intended use:

Thermal insulation products for building equipment and industrial installations

Level(s) or class(es) reaction to fire:

for uses subject to regulations on reaction to fire A2 and A2L. Products for which a clearly identifiable stage in the production process results in an improvement in the reaction to fire classification by limiting of organic material.

Product			Reaction to fire EN 13501-1				
No.	Form	Name	Description	Classification	Range	Fire Group	Classification report
1	Pipe section	<b>Teclit PS</b>	Non-combustible mineral wool concentrically wound pipe section covered with reinforced aluminium foil	A2L-s1, d0	Do ≤ 300 mm Max. organic content: 3,1 kg/m <sup>3</sup> Density: 100 kg/m <sup>3</sup> ± 15 % Thickness: ≥ 20 mm Production line: ROE2, PU1, PU2	4	230010470-3
2	Pipe section	<b>Teclit PS</b>	Non-combustible mineral wool concentrically wound pipe section covered with reinforced aluminium foil	A2-s1,d0	Do > 300 mm Max. organic content: 2,22 kg/m <sup>3</sup> Density: 100 kg/m <sup>3</sup> ± 15 % Thickness: ≥ 20 mm Production line: ROE2, PU1, PU2	6	230010471-2
3	Pipe section	<b>Rockwool 800</b>	Non-combustible mineral wool concentrically wound pipe section faced with reinforced aluminium foil	A2L-s1, d0	Do ≤ 300 mm Max. organic content: 7,2 kg/m <sup>3</sup> Density: 90 kg/m <sup>3</sup> to 180 kg/m <sup>3</sup> Thickness: ≥ 20 mm and ≤ 50 mm Production line: ROE2, PU1, PU2	13	230008366-4

Product			Reaction to fire EN 13501-1				
No.	Form	Name	Description	Classification	Range	Fire Group	Classification report
4	Pipe section	<b>Rockwool 800</b>	Non-combustible mineral wool concentrically wound pipe section faced with reinforced aluminum foil	A2-s1,d0	Do > 300 mm Max. organic content: 2,22 kg/m <sup>3</sup> Density: 90 kg/m <sup>3</sup> to 119 kg/m <sup>3</sup> Thickness: ≥ 20 mm and ≤ 80 mm Production line: ROE2, PU1	14	230008366-4
5	Pipe section	<b>Rockwool 800</b>	Non-combustible mineral wool concentrically wound pipe section faced with reinforced aluminum foil	A2-s1,d0	Do > 300mm Max. organic content: 5,9 kg/m <sup>3</sup> Density: ≤152 kg/m <sup>3</sup> Thickness: ≤100mm Production line: ROE2, PU2	21	YA-2280-2E-RA-003

Detail information about the insulation products are given in the classification reports

Gräfelweg 03.07.2022

Certification Body



Ralph Alberti

